

Telehandler / Zoom Boom

Used Telehandler Iowa - Telehandlers have numerous names including a teleporter, Cherry picker, telescopic handler or boom lift. This industrial machine is commonly used in a variety of industries and in agriculture. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. Numerous attachments can be placed at the end of the articulating boom to conduct a variety of different jobs. Popular attachments include a muck grab, bucket, winch or pallet forks. The most common telehandler attachment is the pallet forks. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. These machines enable cargo pallets to be unloaded and loaded from a trailer and placed on rooftops, racking or other high and hard to access locations. Typically, high locations would traditionally require a crane; however, telehandlers can facilitate these tasks easily and efficiently. It can be expensive and impractical to rely on a crane or expansive industrial equipment to finish particular tasks. A bucket or bucket grab is the most popular telehandler attachment in the agricultural industry. Moving items from unreachable locations that cannot be completed with a backhoe loader or wheeled loader give telehandlers a huge advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Using one machine to finish numerous jobs saves storage space, money and time. Telehandlers commonly work alongside a crane jib. Various attachments may be used including rotators, dirt buckets, grain buckets and power booms. Three-point linkage and power take-off can be used with agricultural models to make this machine particularly capable. Interestingly enough, the machines' main advantage is also its' biggest limitation. The boom acts as a lever when it extends or raises with heavy loads. Even with rear counterweights, this machine may become unstable from time to time; decreasing the lift capacity when the distance between the center of the load and the front of the wheels or the working radius increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. For instance, a telehandler with a five thousand pound capacity may be capable of safely lifting as little as four hundred pounds fully extended with a low boom angle with a retracted boom. This unit with a 5000 lb. lift capability and retracted boom could support as much as ten thousand pounds after the boom is raised seventy degrees. These machines are equipped with a load chart to help outline which tasks are safely possible. These charts take the boom height, angle and weight into account. Updated telehandler models have computers and sensors. The operator cannot continue once the machine's limits have been reached. They are warned and cut off from accessing the control input. There are front stabilizers that can drastically enhance the machine's lifting capacity while it is stationary. Another option is a stabilizing rotary joint between lower and upper frames, often referred to as a mobile crane that can additionally utilize a bucket. There are compact telehandler models that differ in boom design, size, reach and weight. Telehandlers fall into the compact category if the unit weighs in at 11,000 lbs. or less. A two-stage boom is a popular option for compact models whereas the three or four boom design is common for bigger machines. Compact models rely on a low pivot boom to facilitate better cab visibility as the operator transports loads. There are narrower and smaller dimensions offered with the compact telehandler. Compact telehandlers have a reach capacity ranging between 13 to 20 feet with a lift capacity ranging from 5k to 7k pounds. The versatility of the compact telehandler makes it popular in a variety of applications. This machine can be utilized for carrying tools or as a pick and place unit. Compact units are ideal for cramped locations. Residential applications are common as contractors relish their useful nature with framing applications and where height restrictions come into play. These units can be useful for accessing internal building locations. Compact units are popular in multi-story construction, nurseries, strip malls, landscaping, masonry, garage facilities and erecting steel among other applications. Agri-business and farming

applications rely on telehandlers for a variety of jobs. Telehandlers can be found with two and four-wheel drive and crab steering capabilities. This machine can traverse longer distances with two-wheel drive at higher speeds to facilitate easy travel between worksites. Four-wheel drive units can travel over harder terrain while offering a tighter turning radius. Crab steering enhances the units' maneuverability while allowing each set of wheels to move forty-five degrees to the right or left. Compact telehandlers have varying cab environments. On the lower-end models, a rollover protective cage structure is in place for safety. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. Operators enjoy spacious accommodation for ultimate comfort. Additional options including satellite radio, air conditioning, armrests, cup holders, suspension seats and tilt steering are available. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. These attachments increase the functions the machine is capable of. Ground engaging work is often completed by compact units. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. Light and heavy-duty buckets can be used to move items, augers can plant trees or drill holes, rotating and side-shifting fork carriages facilitate pick-and-place, truss booms are in place for extending reach, sweeping brooms and crane hooks are other popular attachments. Skid steer options are made for compact telehandler designs and ultimate versatility.